

# LECTURE 3: DATA STRUCTURES IN R (contd)

## STAT598z: Intro. to computing for statistics

---

Vinayak Rao

Department of Statistics, Purdue University

### SOME USEFUL R FUNCTIONS

`seq()`, `seq_len()`, `min()`, `max()`, `length()`, `range()`,  
`any()`, `all()`

Comparison operators:

`<`, `<=`, `>`, `>=`, `==`, `!=`

Logical operators:

`&&` , `||` , `!` , `&` , `|` , `xor()`

More on coercion:

`is.logical()`,`is.integer()`,`is.double()`,`is.character()`  
`as.logical()`,`as.integer()`,`as.double()`,`as.character()`

Coercion often happens implicitly in function calls:

In [2]: `sum(rnorm(10) > 0)`

2

## Lists (generic vectors) in R

Elements of a list can be any R object (including other lists)

Lists are created using `list()` :

```
In [3]: car <- list("Ford", "Mustang", 1999, TRUE); length(car)
```

```
4
```

Can have nested lists:

```
In [45]: # car, house, cat and sofa are other lists
house <- "Apartment";
cat   <- list("Calico", "Flopsy", 3L);
sofa  <- "Red"
possessions <- list(car, house, cat, sofa, "3000USD")
```

Or lists containing functions:

```
In [5]: mean_list <- list(mean, "Calculates mean of input");
```

## Lists in R

Elements of a list can be anything (including other lists)

Lists are vectors (but not "atomic vectors")

See: `is.vector()`, `is.list()`, `is.atomic()`

What does concatenating lists do? E.g. `c(car, house)`

What does concatenating a list with a vector do?

What does `unlist()` do?

## The `str()` function

Just as with vectors, can apply `typeof()` and `class()`

Another very useful function is `str()`

Provides a summary of the R object

```
In [43]: str(car)
```

```
List of 4
$ Manufacturer: chr "Ford"
$ Make        : chr "Mustang"
$ Year        : num 1999
$ Petrol       : logi TRUE
```

```
In [7]: people <- c("Alice", "Bob", "Carol")
str(people)
```

```
chr [1:3] "Alice" "Bob" "Carol"
```

## Indexing elements of a list

Use brackets `[ ]` and double brackets `[ [ ] ]`

Brackets `[ ]` return a sublist of indexed elements

```
In [44]: car[1]
```

```
$Manufacturer = 'Ford'
```

```
In [9]: typeof(car[1])
```

```
'list'
```

Double brackets `[ [ ] ]` return element of list

```
In [10]: car[[1]]
```

'Ford'

```
In [11]: typeof(car[[1]])
```

'character'

Vector in double brackets recursively indexes list

```
In [12]: possessions[[1]][[1]]
```

'Ford'

```
In [13]: possessions[[c(1,1)]]
```

'Ford'

## Named lists

Can assign names to elements of a list

```
In [14]: names(car) <- c("Manufacturer", "Make", "Year", "Gasoline")
```

```
In [15]: car
```

**\$Manufacturer**

'Ford'

**\$Make**

'Mustang'

**\$Year**

1999

**\$Gasoline**

TRUE

Equivalently, on definition

```
In [16]: car <- list("Manufacturer" = "Ford", "Make" = "Mustang",
                  "Year" = 1999, "Gasoline" = TRUE )
```

See also `setNames()`

## Accessing elements using names

```
In [17]: car[c("Manufacturer", "Make")] # A two-element sublist
```

**\$Manufacturer**

'Ford'

**\$Make**

'Mustang'

```
In [18]: car[["Year"]] # A length-one vector
```

1999

```
In [19]: car$Year # Shorthand notation
```

1999

```
In [20]: car$year # R is case-sensitive!
```

NULL

## Names

The `names()` function can get/set names of elements of a list

```
In [21]: names(car) # Returns a character vector
```

'Manufacturer' 'Make' 'Year' 'Gasoline'

```
In [22]: names(car)[4] <- "Petrol"; names(car)
```

```
'Manufacturer' 'Make' 'Year' 'Petrol'
```

Names need not be unique or complete

Can remove names using `unname()`

Can also assign names to atomic vectors

## Object attributes

`names()` is an instance of an object attribute

These store useful information about the object

Get/set attributes using `attributes()`

```
In [23]: attributes(car)
```

```
$names =
```

```
'Manufacturer' 'Make' 'Year' 'Petrol'
```

Get/set individual attributes using `attr()`

## Object attributes

Other common attributes: `class`, `dim` and `dimnames`

Many have specific accessor functions e.g. `class()` or `dim()`

You can create your own

- Warning: careful about the effect of functions on attributes

## Matrices and arrays

Are two- and higher-dimensional collections of objects

These have an appropriate `dim` attribute

```
In [24]: my_mat <- 1 : 6 # vector
```

```
In [25]: dim(my_mat) <- c(2,3) # 2 rows and 3 columns
print(my_mat)
```

```
[,1] [,2] [,3]
[1,]    1    3    5
[2,]    2    4    6
```

Equivalently

```
In [12]: my_mat <- matrix(c(1,2,3) , nrow = 2, ncol = 3) # ncol is redundant
print(my_mat)
```

```
[,1] [,2] [,3]
[1,]    1    3    2
[2,]    2    1    3
```

Arrays work similarly

```
In [27]: my_arr <- array(1 : 8, c(2,2,2)); print(my_arr)
```

, , 1
[,1] [,2]
[1,] 1 3
[2,] 2 4
, , 2
[,1] [,2]
[1,] 5 7
[2,] 6 8

## Matrices and arrays

Useful functions include

- `typeof()`, `class()`, `str()`
- `dim()`, `nrow()`, `ncol()`
- `is.matrix()`, `as.matrix()`, ...
- `dimnames()`, `rownames()`, `colnames()`

```
In [5]: dimnames(my_mat) <- list(c("r1", "r2"), c("c1", "c2", "c3"))
print(my_mat);my_mat['r1','c2']
```

c1 c2 c3
r1 1 3 2
r2 2 1 3

3

A vector/list is NOT an 1-d matrix (no dim attribute)

```
In [6]: is.matrix(1 : 6);
```

FALSE

## Use drop() to eliminate empty dimensions

```
In [10]: my_mat <- array(1 : 6, c(2,3,1)) # dim(my_mat) is (2,3,1)  
print(my_mat)
```

```
, , 1  
  
[,1] [,2] [,3]  
[1,] 1 3 5  
[2,] 2 4 6
```

```
In [9]: my_mat <- drop(my_mat) # dim is now (2,3)  
print(my_mat)
```

```
[,1] [,2] [,3]  
[1,] 1 3 5  
[2,] 2 4 6
```

## Indexing matrices and arrays

```
In [15]: print(my_mat); my_mat[2,3] # Again, use square brackets
```

```
[,1] [,2] [,3]  
[1,] 1 3 2  
[2,] 2 1 3  
  
3
```

Excluding an index returns the entire dimension

```
In [21]: print(my_mat[-3,-3])
```

```
[,1] [,2]  
[1,] 1 3  
[2,] 2 1
```

```
In [22]: my_arr[1,,1] # slice along dim 2, with dims 1, 3 equal to 1
```

```
Error in eval(expr, envir, enclos): object 'my_arr' not found
Traceback:
```

Usual ideas from indexing vectors still apply

```
In [ ]: print(my_mat[,c(2,3)])
```

## Column-major order

We saw how to create a matrix from an array

```
In [38]: my_mat <- matrix(1 : 6, nrow = 3, ncol = 2); print(t(my_mat))
```

```
[,1] [,2] [,3]
[1,]    1    2    3
[2,]    4    5    6
```

In R matrices are stored in column-major order (like Fortran , and unlike C and Python )

```
In [33]: print(my_mat[1,2])
```

```
[1] 4
```

## Recycling

Column-major order explains recycling to fill larger matrices

```
In [35]: ones <- matrix(1, nrow = 3, ncol = 3)
```

```
In [39]: my_seq <- matrix(c(1,2,3), nrow = 3, ncol = 3); print(my_seq)
```

```
[,1] [,2] [,3]  
[1,]    1    1    1  
[2,]    2    2    2  
[3,]    3    3    3
```

```
In [46]: print(t(t(my_seq) + c(.1,.2,.3)))
```

```
[,1] [,2] [,3]  
[1,]  1.1  1.2  1.3  
[2,]  2.1  2.2  2.3  
[3,]  3.1  3.2  3.3
```